

The EJB... series of enclosures for control, check, signal, automation, interruption and/or protection units provide an Ex d IIB or Ex d IIB+H2 mode of protection, containing electric and/or electronic equipment and terminals, for the link to the outside circuits.

Specifications

Material	Copper-free aluminium (Cu <0,1%)
IP Rating	IP66/IP67 with flanged joint coated with silicone grease (contact our sales dept. for detailed reference)
Temperature	-50°C to 55°C -50°C to 40°C with intrinsically safe elements "ia" or "ib"
Certification & Approvals	EC-Type Examination Certificate INERIS 00ATEX0021X GOST Certificate POCC IT.ГБ04.В00495
Standards	EN 60079-0 / 60079-1 / 60079-11 / 61241-0 / 61241-1 / 61241-11 IEC 60079-0 / 60079-1 / 60079-11 / 61241-0 / 61241-1 / 61241-11
Ex-code	<p>⊕ II 2 GD Ex d IIB T6/T5/T4/T3 Ex d IIB+H₂ T6/T5/T4/T3 Ex tD A21 IP66 T85°C/T100°C/T135°C/T200°C</p> <p>⊕ II 2(1) GD Ex d [ia] IIB T6 Ex d [ia] IIB+H₂ T6 Ex tD [ia] A21 IP66 T85°C</p> <p>According to European Directive 94/9/EC (ATEX) For Zone 1 / Zone 2, Zone 21 / Zone 22</p>
Surface treatment	Unpainted
Drain plug	The enclosures can be equipped with drain and/or breather devices: ECR-1; ECR-2 type
Entries thread	Metric pitch 1.5, ANSI B1.20.1 NPT, UNI 6125
Standard identification	Identification nameplate is realized in high resistance self-adhesive polyester with thermal transfer inscriptions
Quantity for entries	Maximum quantity of entries per side A/B: check table's references
Quantity for terminals	Maximum quantity of terminals per size in sqmm check table's references
Accessories on Request	Painted Polyurethane finish (standard) RAL 6003 colours External polyurethane customized painting
Main Applications	EJB...- Instruments Housing (Windows) EJB...- Moulded Case Circuit Breakers (MCCB) EJB...- On Load Switches (I) EJB...- Fuse On Load Switches (IF) EJB...- Lighting / Power Distribution Panel (QADL) EJB...- Motor Control Starter (TTB) EJB...- Reverse Motor Control Starter (ITB) EJB...- Star Delta Motor Control Starter (STB)
Note	<p>Bearing in mind the infinite number of combinations between:</p> <ul style="list-style-type: none"> • quantity of terminals, • relevant cross section, • class of temperature, • ambient temperature <p>... we suggest using our software CALCUBOX to set up the compatible terminals strips and entries. A free copy of CALCUBOX is usually supplied together with the CD version of this product Catalogue is also available to download from our website.</p>



EJB...Instruments Housing (Windows)

EJB...Lids may be equipped with inspection windows made of tempered glass. The disposition and number of the windows may change in base to their dimensions and the windows may have square, rectangular, circular shape as specified in the relative table reference.

Customized Instrument Housing EJB... Instrument Housing is suitable for use indoor or outdoor, in corrosive and hazardous due to the presence of gases, vapours and dusts...



EJB...Moulded Case Automatic Circuit Breakers (MCCB)

EJB...Enclosure are compatible with any type of MCCB (Moulded Case Circuit Brakers) when in line with relevant EN/IEC STANDARDS.

EJB... On Load Switthes (I)

EJB...meet the demands of customer oriented On-Load Switches. EJB...Series of Enclosures are suitable to build Ex d low voltage switchboard, in accordance with the heat dissipation listed in the relevant certificates.

EJB... Fuse/On-Load Switches (IF)

EJB... meet the needs of customer oriented Fuse/On-Load Switches. EJB...Series of Enclosures are suitable for the set up and the use of Fuses Switches, in accordance with the heat dissipation listed in the relevant certificates.

EJB...Lighting/Power Distribution Panels (QADL)

EJB...meet the needs of customer oriented Lighting/Power Distribution Panel. EJB...Series of Enclosures are suitable to build Ex d low voltage switchboard, in accordance with the heat dissipation listed in the relevant certificates.

EJB... Motor Control Starter (TTB)

EJB...meet the needs of a customer oriented D.O.L. Motor Control Starter.

EJB... Reverse Motor Control Starter (ITB)

EJB... meet the needs of a customer oriented Reverser Motor Control Starter based.

EJB... Star Delta Motor Control Starter (ITB)

EJB... meet the needs of a customer oriented Star-Delta Motor Control Starter.





Items

TYPE	CODE	A	B	C	D	E	F	G	H	I	L	M	N	ØP	R	Weight [kg]	AA	EE
EJB 2	A.0259.10	298	238	174	230	168	95	135	205	140	250	280	9	M6	20	10,07	12	160 x 220
EJB 3	A.0260.10	412	238	177	340	167	85	136	330	150	250	280	9	M8	20	13,40	18	155 x 330
EJB 3a	A.0260.13	412	238	199	340	167	85	158	330	150	250	280	9	M8	20	13,50	9	155 x 330
EJB 4	A.0261.10	418	302	175	335	220	90	132	300	190	300	320	9	M8	20	17,50	20	210 x 325
EJB 5	A.0262.10	480	300	232	392	209	125	182	350	185	300	320	9	M8	20	20,50	22	200 x 385
EJB 6	A.0263.10	483	408	238	387	310	130	186	355	280	390	420	9	M8	20	33,00	28	300 x 380
EJB 8	A.0265.10	634	365	254	530	262	140	204	495	225	340	370	9	M8	20	36,05	36	250 x 520
EJB 9	A.0266.10	535	468	257	426	363	140	204	410	340	440	470	12	M10	20	40,00	34	350 x 420
EJB 10	A.0267.10	750	366	292	630	250	185	234	580	205	330	360	12	M10	20	48,50	34	240 x 620
EJB 11	A.0268.10	596	505	267	483	394	130	204	445	360	480	510	12	M10	20	53,3	44	380 x 470
EJB 12	A.0269.10	805	455	310	690	335	170	243	640	285	425	450	14	M12	20	73,00	54	325 x 675
EJB 13	A.0270.10	832	607	314	723	500	115	236	630	405	580	620	14	M12	20	106,00	76	470 x 690
EJB 13A	A.0270.13	832	607	400	723	500	205	322	630	405	580	620	14	M12	20	124,00	76	470 x 690

NB The Enclosures are equipped with an inside thermostat that, when environment temperature is ranging from -25°C to -50°C, assure an internal temperature of -25°C min. Alternatively, when inside temperature goes over 40°C the thermostat must cut out the circuit tension.

AA = Max quantity of M32x1,5 Push Botton, Pilot Lamp, Selector Swich Operators, that can be installed on the boxes cover.

EE = Internal mounting plate dimension in mm.

Maximum quantity of entries per sides A/B

Type	EJB 2	EJB 3	EJB 4	EJB 5	EJB 6	EJB 8	EJB 9	EJB 10	EJB 11	EJB 12	EJB 13	EJB 13a
M20 / ½"	9/7	14/7	14/9	27/13	24/18	35/16	27/24	57/21	32/27	61/28	48/32	81/54
M25 / ¾"	9/5	7/3	7/4	14/7	14/10	29/13	24/18	46/18	21/27	40/18	27/18	54/36
M32 / 1"	4/3	6/3	6/4	12/5	12/9	16/17	12/10	29/10	14/12	32/16	23/16	35/24
M50 / 1 ½"	3/2	4/2	4/3	5/2	5/4	7/3	9/9	14/5	6/5	16/7	9/6	18/10
M63 / 2"	2/1	3/1	3/2	4/2	4/3	6/2	4/4	12/4	5/4	12/5	8/5	14/9
M75 / 2 ½"	-	-	-	3/1	3/2	4/2	3/3	5/2	4/3	6/3	6/4	6/4
M80 / 3"	-	-	-	2/1	2/2	3/1	2/2	4/1	3/2	4/2	5/3	5/3
4"	-	-	-	1/1	1/1	2/1	2/2	3/1	2/2	3/1	3/2	5/3

If only one side of the box with entries, the above mentioned quantities may be increased (for cable glands only) with previous check of Italsmea

Indicative maximum quantity of terminals per Size in mm² (For specific quantity contact our sales service)

Size [mm ²]	EJB 2	EJB 3	EJB 4	EJB 5	EJB 6	EJB 8	EJB 9	EJB 10	EJB 11	EJB 12	EJB 13	EJB 13a
2,5	48	84	84	96	96	134	96	100	100	180	180	180
4	48	42	84	96	96	134	96	100	100	180	180	180
6	40	36	68	80	80	90	80	80	80	90	90	90
10	32	26	52	60	60	64	60	60	60	108	108	108
16	-	22	44	48	48	58	48	48	46	90	90	90
25	-	10	16	32	18	36	26	36	36	46	70	70
35	-	10	16	16	18	36	26	36	36	18	70	70
50	-	6	12	12	14	14	16	14	25	12	37	37
70	-	-	-	10	10	10	12	12	18	12	20	20
120	-	-	-	-	8	8	8	8	12	12	17	17
185	-	-	-	-	-	-	-	-	-	8	14	14

EJB.../WIN, Instrument Housing

EJB.../WIN is a customer oriented Instrument Housing based on the feature of EJB...Series of Enclosures that is suitable to build EEx d low voltage switchboards, in accordance with the heat dissipation listed in the relevant certificates.

The control, check, signal, automation, interruption and/or protection units EJB. / . - Series are constituted by Enclosures with Ex d IIB or Ex d IIB+H₂ mode of protection and can be completed with accessories such as: push buttons type PLA, PLC-I, PLC-S, PLF; rotary actuators type PSRC; potentiometers; pilot lamps type PLD; rotary actuators type SRC-1/2, SRC-10/11/12; reset device type PLC-R; etc., containing electric and/or electronic equipment and terminals for the link to the outside circuits.

EJB. / . - Series Lids may be equipped with inspection windows made by tempered glass. The disposition and number of the windows may change in base to their dimensions and the windows may have square, rectangular, circular shape as specified in the relative table reference.

Customized Instrument Housing named EJB.../WIN is suitable for indoor or outdoor use and in locations considered corrosive and hazardous due to the presence of gases, vapours and dusts...



EJB.../WIN...Series Instruments Housing

Code P0263.26	Code P0263.25	Code P0263.19	Code P0263.17
B = Window on cover, applicable glass dim. 40x70 mm.	C = Window on cover, applicable glass dim. 40x200 mm.	D = Window on cover, applicable glass dime. 100x270 mm.	E = Window on cover, applicable glass dim. 175x380 mm.

Compatible Round Window								
Ø mm	70	85	100	120	150	170	190	230
CODE	P0263.44	P0263.42	P0263.41	P0263.39	P0263.38	P0263.37	P0263.36	P0263.35

Other window with customized dimensions are available on request when compatible with certificates

Dimensions

